



CC14V-6U

14" RGB-Monitor-Chassis for 6 U
 30...54 kHz / VGA / SVGA / XGA
 MPR II



CRT

- Size: 14"
- Phosphor: P 22, medium short persistence
- Resolution: 1024 x 768 max. (HxV)
- Dot pitch: 0.28 mm

Video Input

- VGA analogue
- Input impedance: 75 Ohm
- Bandwidth: 85 MHz
- Synch.-Input: H + V separated

Deflection

- H-Frequency: 30...54 kHz
- V-Frequency: 50...120 Hz
- Geometry-distort.: 3.0 mm max.
- Linearity: better than 5%

Power Supply

- 3-pin IEC-Socket, rearside
- Mains voltage: 100 V AC ... 240 V AC
50 Hz / 60 Hz
- Power consumption: < 72 W

Dimensions

- See detailed drawing

Controls

- Push/Turn button for OSD-Menu

Others

- Signal-Input: 1.5 m-Cable with 15-pin HD DSUB-Connector
- Working temp.: 0...50 °C
- Humidity: 10...85% relativ, non-condensing
- Security: TÜV-GS, CE, UL, CUL, FCC-B, DHHS, MPR II, EPA, VESA, NUTEC

Weight

- Total: approx. 13.5 kg