



## CE14V

14" RGB-Monitor in 19" Rack  
 30...54 kHz / VGA / SVGA / XGA



<b>CRT</b> <ul style="list-style-type: none"> <li>• Size: 14"</li> <li>• Phosphor: P 22, medium short persistence</li> <li>• Resolution: max. 1024 x 768 (HxV)</li> <li>• Dot pitch: 0.28 mm</li> </ul>	<b>Dimensions</b> <ul style="list-style-type: none"> <li>• Height: 6U</li> <li>• Width (Frontpanel): 19"</li> <li>• Depth: 380 mm</li> </ul>
<b>Video Input and Synchronization</b> <ul style="list-style-type: none"> <li>• VGA analogue</li> <li>• Input impedance: 75 Ohm</li> <li>• Bandwidth: 85 MHz</li> <li>• Sync.-Input: H + V separated</li> </ul>	<b>Weight</b> <ul style="list-style-type: none"> <li>• Total: approx. 15 kg</li> </ul>
<b>Deflection</b> <ul style="list-style-type: none"> <li>• H-Frequency: 30...54 kHz</li> <li>• V-Frequency: 50...120 Hz</li> <li>• Geometry distort.: 3.0 mm max.</li> <li>• Linearity: 5% max. horiz.</li> <li>• Convergence: Center max. 0.3 mm Edges max. 0.5 mm</li> </ul>	<b>Controls</b> <ul style="list-style-type: none"> <li>• Push/Turn button for OSD-Menue</li> </ul>
<b>Power Supply</b> <ul style="list-style-type: none"> <li>• Mains voltage: 100...240 VAC, 50 Hz / 60 Hz</li> <li>• Power consumption: &lt; 80 W</li> </ul>	<b>Others</b> <ul style="list-style-type: none"> <li>• Signal input: 1.5 m-Cable with 15-pin HD DSUB-connector</li> <li>• Working temp.: 0...50 °C</li> <li>• Humidity: 10...85% relativ, non-condensing</li> <li>• Security: TÜV-GS, CE, UL, CUL, FCC-B, DHHS, EPA, VESA, NUTEC</li> </ul>