



## CE15V

15" RGB-Monitor - 19" Rack / 7 U  
VGA / SVGA / XGA/SXGA/1280x1024 max.



### CRT

- Size: 15"
- Phosphor: P22, medium short persistence
- Resolution max.: 1280 x 1024 (HxV)
- Dot pitch: 0.28 mm

### Video input and Synchronization

- VGA analogue
- Input impedance: 75 Ohm
- Bandwidth: 100 MHz
- Sync.-Input: H + V separated

### Deflection

- H-Frequency: 30...70 kHz
- V-Frequency: 50...120 Hz (auto)
- Geometry distort.: 3.0 mm max.
- Linearity: 5% max. horiz.
- Convergence: Center max. 0.3 mm  
Edge max. 0.5 mm

### Power supply

- Mains voltage: 100...240 VAC;  
50-60 Hz
- Power consumption: < 85 W

### Others

- Signal connector: 1.5 m cable with  
15-pin. HD DSUB-  
Connector
- Temperature range: 0 ...50 °C
- Humidity: 10...85% relativ,  
non condensing
- Security: TÜV-GS, CE, UL, CUL  
FCC-B, DHHS, EPA,  
VESA, Nutec

### Dimensions

- Height: 7 U
- Width (Frontpanel): 19"
- Depth: 380 mm

### Weight

- Total: approx. 15 kg

### Controls

- Push-Turn button für OSD-Menue

