



## CE19V

19" RGB-Monitor – 19"-Rack / 9 U  
 30...96 kHz / 1920 x 1440 max.



CRT	
• Size:	19" flat-high-contrast antistatic anti-reflective
• Phosphor:	P22
• Resolution:	max. 1920 x 1440 (HxV)
• Dot pitch:	0.25
Video Input and Synchronization	
• VGA analogue	
• Impedance:	75 Ohm
• Bandwidth:	203 MHz
• Sync.:	H and V separate Composite Sync.
Deflection	
• Horizontal:	30...96 kHz
• Vertical:	50...160 Hz (auto)
Power Supply	
• Power voltage:	95...264 V AC 50Hz/60Hz
• Power consumption:	< 95 W

Dimensions	
• Height:	9 U
• Width (Frontpanel):	19"
• Depth:	470 mm
Weight	
• Total:	approx. 24 kg
Controls	
• Keys:	Brightness and contrast
• OSD:	Zoom, H/V-Position Balance, Trapezoid, Color, Moire, Resolution, Reset etc.
Environmental	
• Working temp.:	0...50 °C
• Humidity:	5...90%RH non-condensing
• Security:	TÜV-GS, CE, FCC-B, UL, CSA, SEMCO, PSB, VCC, DHHS, BCIQ, TCO99, MPRII

