

CEFD 12V-1U

12.1" Color-Display
 with AT-compatible keyboard
 in 19"-drawer 1 U



Display

- Color-TFT-LCD panel
- Display area: 12.1"
- Resolution: max. 800 x 600 Pixel (HxV)
- Dot pitch: 0.3075 x 0.3075 mm
- Color depth: 6 Bit
- Brightness: max. 300 cd/m²

Video Signal

- Connector: 15-pin DSUB (female),
rearside
- Resolutions

640x350	70Hz	31.46kHz
640x400	56Hz	24.80kHz
640x400	70Hz	31.46kHz
640x480	60Hz	31.46kHz
640x480	73Hz	37.86kHz
640x480	75Hz	37.50kHz
640x480	70Hz	37.10kHz
640x480	66Hz	35.00kHz
720x400	70Hz	31.46kHz
800x600	56Hz	35.15kHz
800x600	60Hz	37.87kHz
800x600	72Hz	48.07kHz
800x600	75Hz	46.87kHz
800x600	70Hz	47.80kHz

Power Supply

- Supply voltage: 90 V AC ... 260 V AC
50 Hz / 60 Hz
- Power consumption: max. 20 W

Adjustments

- OSD (On screen display)
- Auto-Adjust
- Contrast
- Brightness
- Phase
- H-Position
- V-Position
- All settings are stored in a non-volatile memory

Dimensions

closed drawer

- Width: 482.6 mm (19")
- Height: 43.6 mm (1U)
- Depth: 387.0 mm

Weight

- Total: ca. 8.5 kg

Environmental

- Working temp.: 0 ... +50 °C
- Storage temp.: -20 ... +60 °C

Keyboard

- Connector: AT-compatible
- Layout: German
- Number of keys: 85
- IP Protection class: IP65

