



MC09B012D(E)

9" s/w-Monitor-Chassis
 15,625 kHz / BAS / 720 x 240



CRT <ul style="list-style-type: none"> • Size: 9" • Phosphor: P4 or P31 medium short persistence • Resolution: max. 720 x 240 (HxV) non interlaced 	Dimensions <ul style="list-style-type: none"> • Height: 175 mm • Width: 227 mm • Depth: 250 mm
Video Input and Synchronization <ul style="list-style-type: none"> • BAS analogue • Input impedance: 75 Ohm 	Weight <ul style="list-style-type: none"> • Total: approx. 2.8 kg
Deflection <ul style="list-style-type: none"> • H-Frequency: 15.625 kHz \pm 0.3 kHz • V-Frequency: 49..61 Hz • Geometry: 3.0 mm max. • Linearity: 5% max. horiz. • Convergence: Middle max. 0.3 mm Edges max. 0.5 mm 	Controls <ul style="list-style-type: none"> • Potentiometer for brightness and contrast
Power Supply <ul style="list-style-type: none"> • Input voltage: 12 VDC • Power consumption: 14 W max. 	
Environmental <ul style="list-style-type: none"> • Working temp.: 0...55 °C • Humidity: 10...90% relativ, non-condensing 	