

## MC09C012D(E)

9" s/w-Monitor-Chassis  
 15,625 kHz / TTL / 720 x 240



<b>CRT</b> <ul style="list-style-type: none"> <li>• Size: 9"</li> <li>• Phosphor: P4 or P31 medium short persistence</li> <li>• Resolution: max. 720 x 240 (HxV) non interlaced</li> </ul>	<b>Dimensions</b> <ul style="list-style-type: none"> <li>• Height: 175 mm</li> <li>• Width: 227 mm</li> <li>• Depth: 250 mm</li> </ul>
<b>Video Input and Synchronization</b> <ul style="list-style-type: none"> <li>• TTL</li> <li>• Input impedance: 75 Ohm</li> </ul>	<b>Weight</b> <ul style="list-style-type: none"> <li>• Total: approx. 2.8 kg</li> </ul>
<b>Deflection</b> <ul style="list-style-type: none"> <li>• H-Frequency: 15.75 kHz <math>\pm</math> 0.3 kHz</li> <li>• V-Frequency: 49..61 Hz</li> <li>• Geometry: 3.0 mm max.</li> <li>• Linearity: 5% max. horiz.</li> <li>• Convergence: Middle max. 0.3 mm Edges max. 0.5 mm</li> </ul>	<b>Controls</b> <ul style="list-style-type: none"> <li>• Potentiometer for brightness and contrast</li> </ul>
<b>Power Supply</b> <ul style="list-style-type: none"> <li>• Input voltage: 12 VDC <math>\pm</math> 0.6V</li> <li>• Power consumption: 14 W max.</li> </ul>	
<b>Environmental</b> <ul style="list-style-type: none"> <li>• Working temp.: 0...55 °C</li> <li>• Humidity: 10...90% relativ, non-condensing</li> </ul>	