

MC12C012D(E)

12" Monochrome-Monitor-Chassis, TTL
 15.625 kHz / TTL / 720 x 240



CRT <ul style="list-style-type: none"> • Size: 12" • Phosphor: P4 or P31 medium short persistence • Resolution: max. 720 x 240 (HxV) non interlaced 	Dimensions <ul style="list-style-type: none"> • Height: 238 mm • Width: 301.4 mm • Depth: 300 mm
Video Input and Synchronization <ul style="list-style-type: none"> • TTL • Connector: 10-pin Card Edge Type • Input impedance: 75 Ohm 	Weight <ul style="list-style-type: none"> • Total: approx. 5 kg
Deflection <ul style="list-style-type: none"> • H-Frequency: 15.75 kHz \pm 0.3 kHz • V-Frequency: 49...61 Hz • Geometry: 3.0 mm max. • Linearity: 5% max. horiz. • Convergence: Center max. 0.3 mm Edges max. 0.5 mm 	Controls <ul style="list-style-type: none"> • Potentiometer for brightness and contrast
Power Supply <ul style="list-style-type: none"> • Input voltage: 12 VDC \pm 0.6 V • Power consumption: 15 W max. 	
Environmental <ul style="list-style-type: none"> • Working temp.: 0...55 °C • Humidity: 10...90% relativ, non-condensing 	